H¹ concl

of said camera which is obtained by the obtaining device, wherein said display device

displays a pan angle by a direction of a camera symbol.

27.   (Four Times Amended) A method for monitoring an image picked up

by a camera connected to a network, comprising the steps of:

obtaining information concerning parameters of the camera including

unchanging parameters and parameters whose conditions are changed by user's operation in

H² concl.

accordance with starting up a monitoring terminal and obtaining information concerning said

parameters whose conditions are changed by user's operation except for said unchanging

parameters of the initial parameters of said camera after the initial startup;

displaying on a screen, the camera-status on the basis of the parameters of said

camera which are obtained by the obtaining step; and

displaying a pan angle by a direction of a camera symbol.

43.   (Four Times Amended) A computer readable medium of monitoring

terminals for monitoring an image picked up by a camera having computer usable program

said program comprising the steps of:

obtaining information concerning parameters of the camera including

H³ cont'd

unchanging parameters and parameters whose conditions are changed by user's operation

connected to a network in accordance with starting up said monitoring terminal and obtaining

information concerning said parameters whose conditions are changed by user's operation

except for said unchanging parameters of the initial parameters of the camera after the initial

startup;

displaying on a screen, the camera status on the basis of the parameters of said

camera; and

757271 v1